



- plate thickness: 2 mm
- all covers are provided with handles
- all covers are split as of type TE 400 ^{**)}
- all splitted covers provided with lock
- other dimensions upon request (e.g. if R1, R2 larger than max. value)
- possible option hand lever hole (standard shown, left hand operation) ^{*)}

Brake type	A	B	F	C	D	E	H	L	M	N	R1/R2 max.	G	K Ø	Thread rod
TE 160	120	220	190	160	100	8,5	420	620	160	460	65	190	140	bolt Ø16
TE 200	155	220	215	140	120	14	540	700	180	520	50	235	140	M12 x 105
TE 250	175	220	270	180	150	14	580	830	220	610	70	290	140	M12 x 105
TE 315	215	220	317	240	185	14	680	955	270	685	100	330	140	M12 x 105
TE 400	260	260	395	320	233	18	790	1105	320	785	140	395	140	M16 x 105
TE 500	320	280	457	400	290	18	880	1255	395	860	170	420	140	M16 x 105
TE 630	400	280	542	510	360	18	1010	1395	470	925	225	475	140	M16 x 105
TE 710	450	280	595	590	405	18	1110	1530	535	995	265	530	140	M16 x 105

When ordering advise: **drum brake type**
dimension R1
dimension R2